

ANNEX 1

KNITTING TECHNOLOGY

Second Edition

A Comprehensive Handbook and
Practical Guide to
Modern Day Principles and Practices

DAVID J. SPENCER

*School of Textile and Knitwear Technology
Leicester Polytechnic, UK*



PERGAMON PRESS

OXFORD · NEW YORK · SEOUL · TOKYO

Knitting Technology

In single-faced structures it can only be produced on machines whose feeds or needles have a reciprocating action so that the yarn only passes across needles which are knitting, otherwise a float stitch would be produced. Held stitches of this type are used for producing three-dimensional shaping such as heel and toe pouches for footwear, held loop shaping on flat machines and designs in solid colour intarsia. Held stitches are produced in double-faced structures by holding loops on one bed whilst continuing to knit on the other thus producing horizontal welt and cord effects.

9.2

The Drop or Press-off Stitch

A drop stitch fault will result if a needle releases its old loop without receiving a new one, sometimes this technique is used to achieve a press-off on all needles in a set between garment length sequences. A drop stitch or press-off stitch is used very occasionally in flat knitting to cause certain loops in a plain structure to be much larger than the rest. Knitting takes place on only one bed of needles and selected needles in the other bed pick up loops which are immediately pressed-off by not receiving a new yarn. The yarn from the pressed-off loops flows into the adjacent loops in the other bed making them larger, giving the impression of a much coarser gauge. Drop stitch wales are sometimes used to provide a guide for the cutting operation. A secure structure is only produced when a needle retains its old loop if it does not receive a new loop.

9.3

The Float Stitch




Fig. 9.1.

A float stitch (Fig. 9.1) is composed of a held loop, one or more float loops and knitted loops. It is produced when a needle (M) holding its old loop fails to receive the new yarn which passes, as a float loop, to the back of the needle and to the reverse side of the resultant stitch, joining together the two nearest needle loops knitted from it.

The float or welt stitch (Fig. 9.2) shows the missed yarn floating freely on the reverse side of the held loop which is the technical back of single jersey structures, but is the inside of rib and interlock structures. The float extends from the base of one knitted or tucked loop to the next and is notated either as an empty square or as a by-passed point, it is assumed that the

Stitches Produced by Varying the Timing of the Needle Loop Intermeshing

s whose
y passes
ould be
-dimen-
old loop
stitches
one be
welt and

without
press-off
stitch of
e certain
ing take
other be
ng a new
ent loop
a much
e a guide
d when





Fig. 9.2.

osed of
oops and
a needle
ceive the
oat loop
he revera
together
d from is
1.2) show
on the
ich is the
ctures, be
structure
se of op
ext and
are or
l that the

Float plating pro-
duces an openwork
structure in single
y and involves
feeding two yarns in a
relationship to
needles having forward
locks (Fig. 9.3). A
heavy yarn (A), for
example, 30 denier, is
fed at a high level and
only received by
needles selected to that
height whereas the fine
yarn (B), possibly 15
denier, is fed at a lower
level and is received
by every needle. Two course

Float Plating 9.4

